

121
100



Fig. 1



1. The first part of the drawing shows a shaft with a diameter of 1.5 inches, supported by bearings. The shaft is connected to a housing with a diameter of 2.5 inches. The housing is made of cast iron and has a thickness of 0.5 inches. The shaft is made of steel and has a length of 1.5 inches. The bearings are made of bronze and have a diameter of 1.5 inches. The housing is supported by a base with a diameter of 3.5 inches. The base is made of cast iron and has a thickness of 1.0 inch. The shaft is connected to a gear with a diameter of 1.5 inches. The gear is made of steel and has a thickness of 0.5 inches. The gear is supported by a housing with a diameter of 2.5 inches. The housing is made of cast iron and has a thickness of 0.5 inches. The gear is connected to a shaft with a diameter of 1.5 inches. The shaft is supported by bearings with a diameter of 1.5 inches. The bearings are made of bronze and have a length of 1.0 inch. The shaft is made of steel and has a length of 1.5 inches. The housing is supported by a base with a diameter of 3.5 inches. The base is made of cast iron and has a thickness of 1.0 inch.

PROPERTY CARD

1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70
71	72	73	74	75	76	77	78	79	80
81	82	83	84	85	86	87	88	89	90
91	92	93	94	95	96	97	98	99	100

PROPERTY CARD

1. The first part of the drawing shows a shaft with a diameter of 1.5 inches, supported by bearings. The shaft is connected to a housing with a diameter of 2.5 inches. The housing is made of cast iron and has a thickness of 0.5 inches. The shaft is made of steel and has a length of 1.5 inches. The bearings are made of bronze and have a diameter of 1.5 inches. The housing is supported by a base with a diameter of 3.5 inches. The base is made of cast iron and has a thickness of 1.0 inch. The shaft is connected to a gear with a diameter of 1.5 inches. The gear is made of steel and has a thickness of 0.5 inches. The gear is supported by a housing with a diameter of 2.5 inches. The housing is made of cast iron and has a thickness of 0.5 inches. The gear is connected to a shaft with a diameter of 1.5 inches. The shaft is supported by bearings with a diameter of 1.5 inches. The bearings are made of bronze and have a length of 1.0 inch. The shaft is made of steel and has a length of 1.5 inches. The housing is supported by a base with a diameter of 3.5 inches. The base is made of cast iron and has a thickness of 1.0 inch.

Fig. 2

PROPERTY CARD

1. The first part of the drawing shows a shaft with a diameter of 1.5 inches, supported by bearings. The shaft is connected to a housing with a diameter of 2.5 inches. The housing is made of cast iron and has a thickness of 0.5 inches. The shaft is made of steel and has a length of 1.5 inches. The bearings are made of bronze and have a diameter of 1.5 inches. The housing is supported by a base with a diameter of 3.5 inches. The base is made of cast iron and has a thickness of 1.0 inch. The shaft is connected to a gear with a diameter of 1.5 inches. The gear is made of steel and has a thickness of 0.5 inches. The gear is supported by a housing with a diameter of 2.5 inches. The housing is made of cast iron and has a thickness of 0.5 inches. The gear is connected to a shaft with a diameter of 1.5 inches. The shaft is supported by bearings with a diameter of 1.5 inches. The bearings are made of bronze and have a length of 1.0 inch. The shaft is made of steel and has a length of 1.5 inches. The housing is supported by a base with a diameter of 3.5 inches. The base is made of cast iron and has a thickness of 1.0 inch.

1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30
31	32	33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48	49	50
51	52	53	54	55	56	57	58	59	60
61	62	63	64	65	66	67	68	69	70
71	72	73	74	75	76	77	78	79	80
81	82	83	84	85	86	87	88	89	90
91	92	93	94	95	96	97	98	99	100